



DC Power Cables

Cat. No.	Description	Roll Size <i>m</i>	Area of Conductor <i>mm²</i>	Conductor No./Diameter <i>mm</i>
3T-30	3mm Twin Fig 8	30	1.13	16/0.3
3T-100	3mm Twin Fig 8	100	1.13	16/0.3
4T-30	4mm Twin Fig 8	30	1.84	26/0.3
4T-100	4mm Twin Fig 8	100	1.84	26/0.3
5S-30	5mm Single (Red or Black)	30	2.90	41/0.3
5S-100	5mm Single (Red or Black)	100	2.90	41/0.3
6S-30	6mm Single (Red or Black)	30	4.59	65/0.3
6S-100	6mm Single (Red or Black)	100	4.59	65/0.3
3DS-100	3mm Twin Double Sheath	100	1.13	16/0.3
4DS-30	4mm Twin Double Sheath	30	1.84	26/0.3
4DS-100	4mm Twin Double Sheath	100	1.84	26/0.3
5DS-30	5mm Twin Double Sheath	30	2.90	41/0.3
5DS-100	5mm Twin Double Sheath	100	2.90	41/0.3
6DS-30	6mm Twin Double Sheath	30	4.59	65/0.3
6DS-100	6mm Twin Double Sheath	100	4.59	65/0.3
FPC6B-100	6mm ² Single Core Black	100	6.00	192/0.2
FPC6R-100	6mm ² Single Core Red	100	6.00	192/0.2
FPC10B-100	10mm ² Single Core Black	100	10.00	322/0.2
FPC10R-100	10mm ² Single Core Red	100	10.00	322/0.2

Speaker Cables

Cat. No.	Description	Roll Size <i>m</i>	Conductor Description <i>mm</i>
SPK-14	Light Duty Fig 8	100	14/0.14
SPK-24	Heavy Duty Fig 8	100	24/0.2

